



- * Water Based
- * Water Resistant
- * Nearly Invisible
- * Stain Resistant

SPECIFICATIONS:

TYPE: Potassium Methyl Silicate modified with Siloxane.

APPEARANCE: Slightly opaque

FINISH: Nearly invisible

CLEAN-UP: Soap & water.

VOC: 0 grams/liter

PH: 10

FLASH POINT: Above 212 degrees.

SHELF LIFE: Two years minimum when stored at room temperature, and unopened.

DESCRIPTION: PENETRATING

SEALER 404 is a water based sealer for use on all types of stone products where you want to maintain the natural finish of the stone without adding a matte or gloss look to the surface. This is great for concrete, brick and other stone products which you don't want to alter the finish but need water protection. 404 is a great grout release. 404 outperformed all other siloxane and potassium silicate type invisible sealers tested. If you have not used 404 Penetrating Sealer, try some on a test sample and see it is the effect you desire. 404 may slightly darken surface, but will maintain the unfinished look.

USES: Use on bricks, pavers, concrete, unglazed tile, grout, granite, stucco, slate and stone products. This is an indoor/ outdoor product.

DIRECTIONS: When applying, clean surface well and let completely dry. Apply 404 with a brush, cloth or a roller. Work liberally into surface and let dry. Apply another coat for further protection. Surface is well sealed when

you reapply and 404 stays on the surface. Wipe excess clean and let dry. Maximum curing time occurs in 24 hours although water resistance will be apparent within a short period of time.

COVERAGE: One gallon of 404 Penetrating Sealer will cover between 150 and 200 feet depending on how porous the surface is.

LIMITS: Do not use below 45 F. When testing for desired results, be sure to allow 24 hours for curing.

CAUTION: Use rubber gloves when applying. Avoid contact with skin. Prolonged exposure to vapors may be harmful or fatal. Use in well ventilated area. In conditions which do not permit good ventilation, use of a breathing apparatus is recommended. Corrosive and irritating to skin and eyes.

NOTICE: Our only obligation shall be to refund the purchase price or replace any of our product proven to be defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product "as is" and without warranties either expressed or implied. The suitability of this product for an intended use shall be solely up to the user.

SHIPPING: Class 55 for water based paint and related products.

PACKAGING: 12 quarts per case, 4 gallons per case and 5 gallon pails.

STORE: Above 40 F. DO NOT FREEZE.

Product of: Duro Shine Sealers llc
P.O. Box 5358
North Hollywood, Ca. 91616

818 982-6412
818 982-8662

www.duroshine.com