

686 PLUS

ULTRA HIGH GLOSS

WATER BASE WET LOOK SEALER - FINISH

- * oil resistant * water resistant
- * self-crosslinking * stain resistant
- * for high traffic * indoor/ outdoor

MADE IN THE U.S.A.

SPECIFICATIONS: Milky white when applied, but dries clear.

FINISH: Ultra High Gloss

CLEAN-UP: Soap and water.

VOC: < 100 grams/liter

FLASH POINT: ABOVE 175 degrees.

SHELF LIFE: Two years minimum when stored at room temperature, and unopened.

DESCRIPTION: ULTRA HIGH GLOSS 686 PLUS is a Self-Crosslinking Acrylic /Polyurethane low V.O.C. Sealer that has great chemical resistance, early water-resistance, and good hot tire resistance. **686 PLUS** has a v.o.c. below 100 which meets all Socal A.Q.M.D. requirements. It performs like, and looks like oil based lacquer, but it is water based, and a breathable sealer. Use **686 PLUS** in areas where hydrostatic pressure exists. This product makes oil based lacquer obsolete. **686 PLUS** meets, or beats the performance any product in gloss, depth of shine, protection and hardness. And it is easy to work with, and no overwhelming, or depressing heavy odors.

ULTRA HIGH GLOSS 686 PLUS is both a sealer and decorative finish for use on porous surfaces like stone, masonry, paver tiles, brick, clay and concrete. It provides a hard shell water resistant shiny finish that gives the appearance of a wet ceramic glaze. The results are revolutionary compared with other oil, or water based products.

If you have not used **686 PLUS** before; try some on a test sample to see that it is the effect you desire. If more traction is needed; an anti-skid agent can be added.

USES: Use on bricks, pavers, concrete, unglazed tile, slate, stone, clay, rock and other porous products. This water based self-crosslinking semi-gloss sealer is the best plastic film forming semi-gloss sealer on the market for indoor, and outdoor.

DIRECTIONS: When applying **ULTRA HIGH GLOSS 686 PLUS** on paver tiles; first install tiles then clean well and let dry. Apply **686 PLUS** with a brush, sprayer or roller, or sponge mop.

Be sure to work first coat into tiles so sealer penetrates deep into tile. When visibly dry; apply light coat. If the surface darkens like it is getting wet, it is not sealed yet, and needs another coat. When you apply the coat where the surface

does not darken like it is wet; it is sealed.

Let dry over night. Grout the pavers. Wait for grout to cure, then after cleaned and dry; again apply **ULTRA HIGH**

GLOSS 686 PLUS as above to the grout and stone. Work in well into grout. **686 PLUS** will help strengthen grout as well as add to the beauty. Extra coats will add to the depth of shine. Allow 48 to 72 hours for the surface to cure. Walk on traffic in 4 hours.

DO NOT APPLY SEALER UNLESS THE SURFACE IS COMPLETELY DRY AND NEUTRALIZED FROM ANY ACID USE.

For use on brick and stone; above directions apply.

COVERAGE: One gallon of **ULTRA HIGH GLOSS 686**

PLUS will cover approximately 200 to 250 square feet per gallon, depending on how porous the surface is. That is how much sealer we estimate on an average surface to get it totally sealed.

COVERAGE: One gallon of **686 PLUS ULTRA HIGH GLOSS** will cover approximately 150 to 250 square feet, depending on how porous the surface is.

LIMITS: Do not use below 45°. Do not let **686 PLUS** puddle or run down vertical surfaces. When testing for desired results be sure to allow 72 hours for curing.

CAUTION: Use rubber gloves when applying. Avoid contact with skin. Prolonged exposure to vapors may be harmful or fatal. Use in a well ventilated area. In conditions which do not permit good ventilation; use of a breathing apparatus is recommended.

NOTICE: Our only obligation shall be to refund purchase price or replace any of our product proved to be defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product "as is" and without warranties either expressed or implied. The suitability of the product for an intended use shall be solely up to the user.

SHIPPING: Class 55 for water based paint and related products.

Packaging: 12 quarts to a case, 4 gallons to a case and 5 gallon pails.

STORE ABOVE 40 F DO NOT FREEZE

Product of: Duro Shine Sealers

**P.O. Box 5358
North Hollywood, Cal. 91606**

**818 982-6412
818 982-8662 fax**

www.duroshine.com